

XGARD BRIGHT

Addressable Fixed Point Gas Detector with Display

Non-intrusive calibration
 MODBUS, HART & relay options



Xgard Bright is a versatile platform offering flammable and toxic gas detection and oxygen monitoring, while providing ease of operation and reduced installation costs.

Lowering the cost of installation, the 4-wire addressable implementation drastically reduces cabling requirements. The large OLED display allows users to easily work with Xgard Bright during install, calibration and routine maintenance without the need to open the housing.

FEATURES

Non-intrusive Calibration

Zero and calibration functions (plus set-up, tests and adjustments) are performed via the display using the magnetic wand, without needing to open the housing reducing the need for a hot-work permit.

OLED Display

The brightly illuminated “organic light emitting diode” display clearly indicates the gas level and units as well as providing comprehensive menus for set-up and diagnosis. In low ambient light conditions, such as a dark room, the OLED display achieves a much higher contrast ratio than an LCD used on conventional gas detectors.

Addressable Communications

Xgard Bright detectors can be connected on an addressable network using RS-485 Modbus. This option significantly reduces cable and installation costs, whilst increasing the flexibility and functionality of the wider system.

Long-life Sensors

Select from durable sensor options such as MPS (10+ years), O2 Long-life (5 years) and IR sensors (10+ years) to prevent frequent sensor replacements and minimise operational expenses.

GAS RANGES & ALARMS

GAS	SENSOR	RANGES AVAILABLE
Range of flammable gases*	MPS	0-100% LEL
Hydrogen sulphide (H ₂ S)	Electrochemical	10, 20, 25, 50, 100, 200 ppm
Oxygen (O ₂)	Oxygen (O2) Long Life (Lead free)	0-25% vol
Oxygen (O ₂)	Oxygen (O2)	0-25% vol
Carbon Monoxide (CO)	Electrochemical	0-25, 50, 100, 200, 250, 300, 1000, 2000 ppm
Methane (CH ₄)	Pellistor	0-100% LEL
Pentane (C ₅ H ₁₂)	Pellistor	0-100% LEL
Hydrogen (H ₂)	Pellistor	0-100% LEL
LPG	Pellistor	0-100% LEL
Carbon Dioxide (CO ₂)	Infrared	0-5% vol
VOC*	PID	0-1000 PPM
Methane (CH ₄)	Infrared	0-100% LEL
Propane (C ₃ H ₈)	Infrared	0-100% LEL
Ammonia (NH ₃)**	Electrochemical	0-50, 100 ppm
Chlorine (Cl ₂)**	Electrochemical	0-5, 10 ppm
Ozone (O ₃)**	Electrochemical	0-1 ppm
Sulphur dioxide (SO ₂)**	Electrochemical	0-10 ppm
Butane (C ₄ H ₁₀)	Infrared	0-100% LEL
Pentane (C ₅ H ₁₂)	Infrared	0-100% LEL
LPG	Infrared	0-100% LEL
Hydrogen Cyanide (HCN)**	Electrochemical	0-25 ppm
Hydrogen Peroxide (H ₂ O ₂)**	Electrochemical	0-5 ppm

* Contact Crowcon for more information
 ** Safe Area Only

SPECIFICATIONS

ENCLOSURE MATERIAL	ADC 12 aluminium alloy or 316 stainless steel	
DIMENSIONS	Aluminium enclosure: 156 x 166 x 109mm (6.1 x 6.5 x 4.3inch) Stainless Steel Enclosure: 161 x 166 x 105mm (6.1 x 6.5 x 4.3inch)	
WEIGHT	Aluminium alloy 1kg (2.2lbs) Stainless Steel: 3.1 kg (6.8lbs) approx.	
INGRESS PROTECTION	IP65 & IP66 (with weatherproof cap)	
CABLE ENTRY	2x M20 (stopping plug fitted to left-side entry) or 2x ½" NPT ports (stopping plug fitted to left-side entry)	
POWER	10-30Vdc. 3W max	
ELECTRICAL OUTPUT	4-20mA current sink or source RS-485 Modbus RTU HART (optional)	
RELAYS	Alarm 1, Alarm 2, Fault SPST contacts rated 1A 30Vdc	
SOUNDER OUT	24Vdc (nominally), 250mA maximum load	
OPERATING TEMPERATURE	-40°C to +70°C (-40°F to 158°F) Note: sensor operating temperatures vary widely Refer to the sensor module datasheet or contact Crowcon for specific sensor data.	
HUMIDITY	0 to 95% RH, non-condensing	
REPEATABILITY	+/- 2% FSD	
ZERO DRIFT	+/- 2% FSD per year maximum	
APPROVAL CODES	<p>ATEX (Aluminium): Ex II 2 G Ex db IIC T6 Gb -40°C≤Ta≤70 °C Ex II 2 D Ex tb IIIC T80°C Db</p> <p>ATEX (Stainless Steel): Ex II 2 G Ex db IIC T3 Gb -40°C≤Ta≤70 °C Ex II 2 G Ex db IIC T4 Gb -40°C≤Ta≤50°C Ex II 2 D Ex tb IIIC T80°C Db</p>	<p>IECEX (Aluminium): Ex db IIC T6 Gb -40°C≤Ta≤70 °C Ex tb IIIC T80°C Db</p> <p>IECEX (Stainless Steel): Ex db IIC T3 Gb -40°C≤Ta≤70°C Ex db IIC T4 Gb -40°C≤Ta≤50°C Ex tb IIIC T80°C Db</p> <p>Certificate numbers: TUV 16 ATEX 7908 X IECEX TUR 16.0035 X</p>
STANDARDS	IEC 60079-0:2017 Ed.7.0; EN IEC 60079-0:2018; IEC 60079-1:2014 Ed.7.0; EN 60079-1:2014; IEC 60079-31:2013 Ed.2.0; EN 60079-31:2014	
ZONES	Certified for use in Zone 1 and Zone 2 areas	
EMC COMPLIANCE	EN50270:2015	

Disclaimer

Due to ongoing research and product improvement, specifications are subject to change without notice. While every effort has been made to ensure accuracy in this document, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This document is not intended to form the basis of a contract.

For more information:

t: +44 (0)1235 557700
e: info@crowcon.com
w: www.crowcon.com

Locate your Regional Sales Representative at:
www.crowcon.com/contact-us/where-to-buy

© 2024 Crowcon Detection Instruments Ltd.